

TCPWM (Timer / Counter mode) example project

3.0

Features

- TCPWM component configured as Timer/Counter
- Underflow (Terminal Count) interrupt blinks LED
- Capture-interrupt selects which LED to blink

General Description

This example project demonstrates the usage of the TCPWM component configured as Timer/Counter with two interrupts enabled: Capture and Underflow (Terminal Count).

Development kit configuration

This example project is designed to run on the CY8CKIT-042 kit from Cypress Semiconductor. A description of the kit, along with more example programs and ordering information, can be found at <http://www.cypress.com/go/cy8ckit-042>.

The project requires configuration settings changes to run on other kits from Cypress Semiconductor. Table 1 is the list of the supported kits. To switch from CY8CKIT-042 to any other kit, change the project's device with the help of Device Selector called from the project's context menu.

Table 1. Development Kits vs Parts

Development Kit	Device
CY8CKIT-042	CY8C4245AXI-483
CY8CKIT-040	CY8C4014LQI-422
CY8CKIT-042-BLE	CY8C4247LQI-BL483
CY8CKIT-044	CY8C4247AZI-M485
CY8CKIT-046	CY8C4248BZI-L489
CY8CKIT-041	CY8C4045AZI-S413 / CY8C4146AZI-S433
CY8CKIT-048	CY8C4A45LQI-483

The pins assignment for the supported kits is in Table 2.

Table 2. Pins Assignment

Pin Name	Development Kit						
	CY8CKIT-042	CY8CKIT-040	CY8CKIT-042 BLE	CY8CKIT-044	CY8CKIT-046	CY8CKIT-041	CY8CKIT-048
LED_GREEN	P0[2]	P1[1]	P3[6]	P2[6]	P5[3]	P2[6]	P2[6]
LED_BLUE	P0[3]	P0[2]	P3[7]	P6[5]	P5[4]	P3[6]	P1[6]

CaptureSource	P2[0]						
CaptureInput	P0[1]	P0[1]	P0[1]	P0[1]	P0[1]	P0[1]	P4[0]

To observe the project operation, perform the following steps:

1. Connect P2[0] to P0[1] to connect the Capture Source and Capture Input.
2. Build the project and program the hex file on to the target device.
3. Power on the device and observe the blinking LED change the color upon every Capture interrupt.

Project configuration

The example project consists of the following components: TCPWM, Clock, three digital output pins, digital input pin, and interrupt. The TCPWM is used as the Down Timer with the Capture mode in the Continuous Run mode. One output pin is used for the Capture signal generation (could be replaced with the user switch). That output CaptureSource pin should be connected to the CaptureInput pin with a wire. Two output pins are used to control the LEDs reflecting the Underflow (Terminal Count) and Capture events.

Project description

In the project, TCPWM counts the value from 65000u down to 0u. When the counter reaches the zero value, an interrupt happens and the active LED toggles. Every 3 seconds, the CaptureSource signal generates a pulse causing a Capture interrupt and the LED color then toggles between blue and green.

Expected results

The LED blinks once per second, and toggles upon the Underflow (Terminal Count). The LED color changes once every 3 seconds when a Capture interrupt occurs. If we disconnect the wire between CaptureSource and CaptureInput, and connect the CaptureInput to GND, the Capture interrupt won't be generated and the LED will blink with the same color. Alternatively, the user switch can be connected to CaptureInput to change the color upon each button press (CaptureInput drive mode must be changed to Resistive Pull-Up).





Cypress Semiconductor
198 Champion Court
San Jose, CA 95134-1709

Phone : 408-943-2600
Fax : 408-943-4730
Website : www.cypress.com

© Cypress Semiconductor Corporation, 2009-2016. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

PSoC® is a registered trademark, and PSoC Creator™ and Programmable System-on-Chip™ are trademarks of Cypress Semiconductor Corp. All other trademarks or registered trademarks referenced herein are property of the respective corporations.

Any Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.

